

Stanley Access Technologies

Stan-Cam™ Color Video Camera

- Provides a continuous video signal of the area around the door opening including the threshold.
- Easily integrates with SU-100 motion sensor to provide a camera view angle of 20 degrees out from the header.
- Provides camera recording capability in area around the door for added liability and security protection.



Stan-Cam



Stan-Cam with SU-100

Add video surveillance to existing SU-100 Sensor for added security protection.

- Compatible with existing security systems
- Size: 5.8" (146.7) wide x 1.3" (32.0) deep x 3.7" (93.9) high
- Coordinating black gloss finish is resistant to UV Light
- Operating Temperature: -30°F to +140°F
- Single chip – ¼" Lens video camera – high sensitivity
- Composite video: NTSC
- Sensitivity Boost (+27dB) AGC on-off
- Automatic Exposure/gain/white balance
- Aperture correction
- 1/3" color CMOS Camera Board
- Picture Elements: 510(H) x 492(V)
- Horizontal Frequency: 14.318MHz
- Vertical Frequency: 60Hz
- Min. Illumination: 2 Lux
- Resolution: 420 TV lines
- Auto Shutter Function: 1/50, 1/60 to 1/15,000 sec
- Gamma Correction: 0.45
- Gain Control: Auto Gain Control
- Power: 6-7 Volt DC (+/- 10%)

Stanley Access Technologies - safe, cost effective, and durable solutions customized for every application.